



PRO SERIES® PhosREMOVE™ Instructions

Directions for use:

1. Backwash filter and maintain proper chemical levels.
2. With the circulation system operating, slowly add product directly to pool, skimmer, gutter or surge tank.
3. Vacuum if required
4. Backwash/ clean filter as necessary (or within 48 hours).

Note: Apply in accordance with your state and local pool regulations. Removing high phosphate levels may temporarily cause pool water cloudiness/turbidity. For high phosphate removal it is recommended to divide the initial dose into at least three separate applications to reduce the possibility of turbid or cloudy water.

RETEST PHOSPHATE LEVELS AFTER 48 HOURS. (Repeat as necessary).

Dosage Chart:

Phosphate reduction varies based on phosphate concentrations. Recommendations are for estimation purposes only. Based on lab test, results may vary.

PPB	10,000 gal	20,000 gal	50,000 gal	100,000 gal	200,000 gal	300,000 gal
1,000	2oz	4oz	10oz	20oz	40oz	60oz
3,700	4oz	8oz	20oz	40oz	80oz	120oz
5,100	8oz	16oz	40oz	80oz	160oz	240oz
7,800	16oz	32oz	80oz	160oz	320oz	480oz
10,000	32oz	64oz	160oz	320oz	640oz	960oz
12,000	48oz	96oz	240oz	480oz	960oz	1440oz

Maintenance Dose:

Weekly add 1oz per 6,000 gallons of pool water.

Important: Algae must be treated prior to testing or treating phosphates. Chlorine must be under 5ppm before testing phosphates.

NOTE: For use in swimming pools only.